
World Housing Encyclopedia

*an Encyclopedia of Housing Construction in
Seismically Active Areas of the World*



an initiative of
Earthquake Engineering Research Institute (EERI) and
International Association for Earthquake Engineering (IAEE)

HOUSING REPORT

Rammed earth house with pitched roof (Nyumba yo dinda OR Nyumba ya mdindo)

Report #	45
Report Date	05-06-2002
Country	MALAWI
Housing Type	Adobe / Earthen House
Housing Sub-Type	Adobe / Earthen House : Rammed earth/Pise construction
Author(s)	Mauro Sassu, Ignasio Ngoma
Reviewer(s)	Manuel A. Lopez M.

Important

This encyclopedia contains information contributed by various earthquake engineering professionals around the world. All opinions, findings, conclusions & recommendations expressed herein are those of the various participants, and do not necessarily reflect the views of the Earthquake Engineering Research Institute, the International Association for Earthquake Engineering, the Engineering Information Foundation, John A. Martin & Associates, Inc. or the participants' organizations.

Summary

This type of construction is used for residences only. The building technique consists of in-situ ramming of moist soil in a carefully aligned/placed mold. The mold dimensions are between (250 - 300 mm) wide X (400 - 450 mm) long X (200 - 300 mm) height. The plan of the house

is rectangular. The roof is either grass thatch or iron sheets supported on timber poles. This type is found in all three regions of Malawi. The strength of the wall is low and depends on the compacting effort applied. The expected seismic performance is poor. There are no vertical or horizontal reinforcements.

1. General Information

Buildings of this construction type can be found in The house type is found in all three regions of Malawi. This house type represents about 35% of total housing stock in Malawi. This type of housing construction is commonly found in rural areas. This construction type has been in practice for less than 100 years.

Currently, this type of construction is being built. .



Figure 1: Typical "nyumba yo dinda" house



Figure 2: Typical Building

2. Architectural Aspects

2.1 Siting

These buildings are typically found in flat terrain. They do not share common walls with adjacent buildings. When separated from adjacent buildings, the typical distance from a neighboring building is 2-3 meters.

2.2 Building Configuration

Rectangular shape. Generally three openings are provided, i.e. one door and two windows. The door is in front and so are the windows. The door is about 1.7 m high X 0.6 m wide. The windows are 0.3 m wide X 0.6 m high. The window and door areas are about 5% of the overall wall surface area.

2.3 Functional Planning

The main function of this building typology is single-family house. In a typical building of this type, there are no elevators and 1-2 fire-protected exit staircases. None.

2.4 Modification to Building

Re-roofing and wall smearing i.e. smearing with specially prepared mud mortar.




Figure 3: Plan and transverse section of a typical building

3. Structural Details

3.1 Structural System

Material	Type of Load-Bearing Structure	#	Subtypes	Most appropriate type	
Masonry	Stone Masonry Walls	1	Rubble stone (field stone) in mud/lime mortar or without mortar (usually with timber roof)	<input type="checkbox"/>	
		2	Dressed stone masonry (in lime/cement mortar)	<input type="checkbox"/>	
	Adobe/ Earthen Walls	3	Mud walls	<input type="checkbox"/>	
		4	Mud walls with horizontal wood elements	<input type="checkbox"/>	
		5	Adobe block walls	<input type="checkbox"/>	
		6	Rammed earth/Pise construction	<input checked="" type="checkbox"/>	
	Unreinforced masonry walls	7	Brick masonry in mud/lime mortar	<input type="checkbox"/>	
		8	Brick masonry in mud/lime mortar with vertical posts	<input type="checkbox"/>	
		9	Brick masonry in lime/cement mortar	<input type="checkbox"/>	
		10	Concrete block masonry in cement mortar	<input type="checkbox"/>	
	Confined masonry	11	Clay brick/tile masonry, with wooden posts and beams	<input type="checkbox"/>	
		12	Clay brick masonry, with concrete posts/tie columns and beams	<input type="checkbox"/>	
		13	Concrete blocks, tie columns and beams	<input type="checkbox"/>	
	Reinforced masonry	14	Stone masonry in cement mortar	<input type="checkbox"/>	
		15	Clay brick masonry in cement mortar	<input type="checkbox"/>	
		16	Concrete block masonry in cement mortar	<input type="checkbox"/>	
			17	Flat slab structure	<input type="checkbox"/>
			18	Designed for gravity loads only, with URM infill walls	<input type="checkbox"/>
			Designed for seismic effects,		

Structural concrete	Moment resisting frame	19	w with URM infill walls	<input type="checkbox"/>	
		20	Designed for seismic effects, w with structural infill walls	<input type="checkbox"/>	
		21	Dual system – Frame with shear wall	<input type="checkbox"/>	
	Structural wall	22	Moment frame with in-situ shear walls	<input type="checkbox"/>	
		23	Moment frame with precast shear walls	<input type="checkbox"/>	
	Precast concrete		24	Moment frame	<input type="checkbox"/>
			25	Prestressed moment frame w with shear walls	<input type="checkbox"/>
			26	Large panel precast walls	<input type="checkbox"/>
27			Shear wall structure with walls cast-in-situ	<input type="checkbox"/>	
28			Shear wall structure with precast wall panel structure	<input type="checkbox"/>	
Steel	Moment-resisting frame	29	With brick masonry partitions	<input type="checkbox"/>	
		30	With cast in-situ concrete walls	<input type="checkbox"/>	
		31	With lightweight partitions	<input type="checkbox"/>	
	Braced frame	32	Concentric connections in all panels	<input type="checkbox"/>	
		33	Eccentric connections in a few panels	<input type="checkbox"/>	
	Structural wall	34	Bolted plate	<input type="checkbox"/>	
35		Welded plate	<input type="checkbox"/>		
Timber	Load-bearing timber frame	36	Thatch	<input type="checkbox"/>	
		37	Walls with bamboo/reed mesh and post (Wattle and Daub)	<input type="checkbox"/>	
		38	Masonry with horizontal beams/planks at intermediate levels	<input type="checkbox"/>	
		39	Post and beam frame (no special connections)	<input type="checkbox"/>	
		40	Wood frame (with special connections)	<input type="checkbox"/>	
		41	Stud-wall frame with plywood/gypsum board sheathing	<input type="checkbox"/>	
		42	Wooden panel walls	<input type="checkbox"/>	
Other	Seismic protection systems	43	Building protected with base-isolation systems	<input type="checkbox"/>	
		44	Building protected with seismic dampers	<input type="checkbox"/>	
	Hybrid systems	45	other (described below)	<input type="checkbox"/>	

3.2 Gravity Load-Resisting System

The vertical load-resisting system is others (described below). The roof is directly supported by the rammed earth wall which in turn rests directly on the ground.

3.3 Lateral Load-Resisting System

The lateral load-resisting system is earthen walls. The wall is made by use of a mould which is placed where the wall will be located. Moist soil is placed in it and rammed using a tamping wooden piece in at least three layers. The process is repeated until the proper height is reached. The wall height is about 2.5 m with a thickness of between 0.20 m and

0.30.

3.4 Building Dimensions

The typical plan dimensions of these buildings are: lengths between 6 and 6 meters, and widths between 4 and 4 meters. The building is 1 storey high. The typical span of the roofing/flooring system is 4 meters. Typical Plan Dimensions: This is only indicative size because the size varies depending on the requirements of the owner. Typical Story Height: The length to width ratio is never less than 2. The typical storey height in such buildings is 2.1 meters. The typical structural wall density is more than 20 %. About 30%.

3.5 Floor and Roof System

Material	Description of floor/roof system	Most appropriate floor	Most appropriate roof
Masonry	Vaulted	<input type="checkbox"/>	<input type="checkbox"/>
	Composite system of concrete joists and masonry panels	<input type="checkbox"/>	<input type="checkbox"/>
Structural concrete	Solid slabs (cast-in-place)	<input type="checkbox"/>	<input type="checkbox"/>
	Waffle slabs (cast-in-place)	<input type="checkbox"/>	<input type="checkbox"/>
	Flat slabs (cast-in-place)	<input type="checkbox"/>	<input type="checkbox"/>
	Precast joist system	<input type="checkbox"/>	<input type="checkbox"/>
	Hollow core slab (precast)	<input type="checkbox"/>	<input type="checkbox"/>
	Solid slabs (precast)	<input type="checkbox"/>	<input type="checkbox"/>
	Beams and planks (precast) with concrete topping (cast-in-situ)	<input type="checkbox"/>	<input type="checkbox"/>
	Slabs (post-tensioned)	<input type="checkbox"/>	<input type="checkbox"/>
Steel	Composite steel deck with concrete slab (cast-in-situ)	<input type="checkbox"/>	<input type="checkbox"/>
Timber	Rammed earth with ballast and concrete or plaster finishing	<input type="checkbox"/>	<input type="checkbox"/>
	Wood planks or beams with ballast and concrete or plaster finishing	<input type="checkbox"/>	<input type="checkbox"/>
	Thatched roof supported on wood purlins	<input type="checkbox"/>	<input checked="" type="checkbox"/>
	Wood shingle roof	<input type="checkbox"/>	<input type="checkbox"/>
	Wood planks or beams that support clay tiles	<input type="checkbox"/>	<input type="checkbox"/>
	Wood planks or beams supporting natural stones slates	<input type="checkbox"/>	<input type="checkbox"/>
	Wood planks or beams that support slate, metal, asbestos-cement or plastic corrugated sheets or tiles	<input type="checkbox"/>	<input type="checkbox"/>
	Wood plank, plywood or manufactured wood panels on joists supported by beams or walls	<input type="checkbox"/>	<input type="checkbox"/>
Other	Described below	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Rammed earth with plaster/smear finishing. Floor is considered to be a flexible diaphragm.

3.6 Foundation

Type	Description	Most appropriate type
Shallow foundation	Wall or column embedded in soil, without footing	<input type="checkbox"/>
	Rubble stone, fieldstone isolated footing	<input type="checkbox"/>
	Rubble stone, fieldstone strip footing	<input type="checkbox"/>
	Reinforced-concrete isolated footing	<input type="checkbox"/>

	Reinforced-concrete strip footing	<input type="checkbox"/>
	Mat foundation	<input type="checkbox"/>
	No foundation	<input checked="" type="checkbox"/>
Deep foundation	Reinforced-concrete bearing piles	<input type="checkbox"/>
	Reinforced-concrete skin friction piles	<input type="checkbox"/>
	Steel bearing piles	<input type="checkbox"/>
	Steel skin friction piles	<input type="checkbox"/>
	Wood piles	<input type="checkbox"/>
	Cast-in-place concrete piers	<input type="checkbox"/>
	Caissons	<input type="checkbox"/>
Other	Described below	<input type="checkbox"/>



Figure 4: Critical structural details



Figure 5: An illustration of key seismic features and/or deficiencies

4. Socio-Economic Aspects

4.1 Number of Housing Units and Inhabitants

Each building typically has 1 housing unit(s). 1 units in each building. The number of inhabitants in a building during the day or business hours is less than 5. The number of inhabitants during the evening and night is less than 5. or 5-10.

4.2 Patterns of Occupancy

Generally one family occupies one housing unit.

4.3 Economic Level of Inhabitants

Income class	Most appropriate type
a) very low-income class (very poor)	<input checked="" type="checkbox"/>
b) low-income class (poor)	<input checked="" type="checkbox"/>
c) middle-income class	<input type="checkbox"/>
d) high-income class (rich)	<input type="checkbox"/>

50% very poor and 50% poor. It is difficult to estimate the ratio of house price/annual income.

Ratio of housing unit price to annual income	Most appropriate type
5:1 or worse	<input type="checkbox"/>
4:1	<input type="checkbox"/>
3:1	<input type="checkbox"/>
1:1 or better	<input checked="" type="checkbox"/>

What is a typical source of financing for buildings of this type?	Most appropriate type
Owner financed	<input checked="" type="checkbox"/>
Personal savings	<input type="checkbox"/>
Informal network: friends and relatives	<input checked="" type="checkbox"/>
Small lending institutions / micro-finance institutions	<input type="checkbox"/>
Commercial banks/mortgages	<input type="checkbox"/>
Employers	<input type="checkbox"/>
Investment pools	<input type="checkbox"/>
Government-owned housing	<input type="checkbox"/>
Combination (explain below)	<input type="checkbox"/>
other (explain below)	<input type="checkbox"/>

In each housing unit, there are 1 bathroom(s) without toilet(s), 1 toilet(s) only and 1 bathroom(s) including toilet(s).

Bathrooms and toilets are externally provided by a small shelter and a pit latrine. .

4.4 Ownership

The type of ownership or occupancy is outright ownership and individual ownership.

Type of ownership or occupancy?	Most appropriate type
Renting	<input type="checkbox"/>
outright ownership	<input checked="" type="checkbox"/>
Ownership with debt (mortgage or other)	<input type="checkbox"/>
Individual ownership	<input checked="" type="checkbox"/>
Ownership by a group or pool of persons	<input type="checkbox"/>
Long-term lease	<input type="checkbox"/>
other (explain below)	<input type="checkbox"/>

5. Seismic Vulnerability

5.1 Structural and Architectural Features

Structural/ Architectural Feature	Statement	Most appropriate type		
		Yes	No	N/A
Lateral load path	The structure contains a complete load path for seismic force effects from any horizontal direction that serves to transfer inertial forces from the building to the foundation.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Building Configuration	The building is regular with regards to both the plan and the elevation.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Roof construction	The roof diaphragm is considered to be rigid and it is expected that the roof structure will maintain its integrity, i.e. shape and form, during an earthquake of intensity expected in this area.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Floor construction	The floor diaphragm(s) are considered to be rigid and it is expected that the floor structure(s) will maintain its integrity during an earthquake of intensity expected in this area.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Foundation performance	There is no evidence of excessive foundation movement (e.g. settlement) that would affect the integrity or performance of the structure in an earthquake.	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wall and frame structures- redundancy	The number of lines of walls or frames in each principal direction is greater than or equal to 2.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wall proportions	Height-to-thickness ratio of the shear walls at each floor level is: Less than 25 (concrete walls); Less than 30 (reinforced masonry walls); Less than 13 (unreinforced masonry walls);	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Foundation-wall connection	Vertical load-bearing elements (columns, walls) are attached to the foundations; concrete columns and walls are doweled into the foundation.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wall-roof connections	Exterior walls are anchored for out-of-plane seismic effects at each diaphragm level with metal anchors or straps	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Wall openings	The total width of door and window openings in a wall is: For brick masonry construction in cement mortar : less than 1/2 of the distance between the adjacent cross walls; For adobe masonry, stone masonry and brick masonry in mud mortar: less than 1/3 of the distance between the adjacent cross walls; For precast concrete wall structures: less than 3/4 of the length of a perimeter wall.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Quality of building materials	Quality of building materials is considered to be adequate per the requirements of national codes and standards (an estimate).	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Quality of workmanship	Quality of workmanship (based on visual inspection of few typical buildings) is considered to be good (per local construction standards).	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Maintenance	Buildings of this type are generally well maintained and there are no visible signs of deterioration of building elements (concrete, steel, timber)	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Additional Comments				

Structural element	Building material	Characteristic strength	Mix proportions/dimensions	Comments
Walls	Rammed earth.	N/A		
Foundation				
Frames (beams & columns)	Timber			
Roof and floor(s)				

6.2 Builder

Yes.

6.3 Construction Process, Problems and Phasing

The house is built by a special master builder who learns the job as an assistant. He learns the job as he helps with bringing the soil (as assistant). A pit is dug and water is poured in it overnight. The soil is only expected to be moist i.e. the soil must not retain the water. The tools used are a hoe, two buckets, a mould, a tamping wooden piece, and a scraper for removing soil from the mould. FOUNDATION: There is no foundation. The lines of the walls are marked on leveled ground, pegs are placed where necessary. WALL CONSTRUCTION: The wall is made of rammed earth. A site of the soil pit is identified with trials to make sure that the soil does not have a lot of clay content. Soil is dug and water poured in it to soak it over night. The moisture of the soil is critical so that remixing is done from time to time. The soil is then moved to the mould which is already placed in the proper place on the construction site. The soil is rammed in layers in the mould. It is necessary to ensure that a proper compacting effort has been achieved before removing the mould. ROOFING: The roof is made up of grass thatch placed on timber poles made into a grid/mesh to retain the grass. The poles are supported on a timber pole beam which is itself supported on two king posts which are supported by timber pole beams spanning across the longitudinal walls. The two beams are placed at 1/4 points from the ends. Once the grass thatch has been placed, small sized timber poles are split and placed above grass and tied to poles below grass so that grass does not move out of place. This is done at 1/3 points all round. OPENINGS: The openings are few. Timber lintels are provided although not strong. The construction of this type of housing takes place in a single phase. Typically, the building is originally not designed for its final constructed size.

6.4 Design and Construction Expertise

Generally good level of expertise based on this practice. No role so far.

6.5 Building Codes and Standards

This construction type is not addressed by the codes/standards of the country.

6.6 Building Permits and Development Control Rules

This type of construction is a non-engineered, and not authorized as per development control rules. Building permits are not required to build this housing type.

6.7 Building Maintenance

Typically, the building of this housing type is maintained by Owner(s).

6.8 Construction Economics

Difficult to estimate because of communal nature of working. The builder, assistant, and others for drawing water from borehole, etc.

7. Insurance

Earthquake insurance for this construction type is typically unavailable. For seismically strengthened existing buildings or new buildings incorporating seismically resilient features, an insurance premium discount or more complete coverage is unavailable.

8. Strengthening

8.1 Description of Seismic Strengthening Provisions

Strengthening of Existing Construction :

Seismic Deficiency	Description of Seismic Strengthening provisions used
Weak lintels	Reinforcing with wood lintels
No ties between roof and wall	Inserting of ties
Weak joining of roof members	Wood transverse connections

Weak lintels Reinforcing with wood lintels. No ties between roof and wall Inserting of ties. Weak joining of roof members Wood transverse connections.

8.2 Seismic Strengthening Adopted

Has seismic strengthening described in the above table been performed in design and construction practice, and if so, to what extent?

No.

Was the work done as a mitigation effort on an undamaged building, or as repair following an earthquake?

Repair following earthquake damage.

8.3 Construction and Performance of Seismic Strengthening

Was the construction inspected in the same manner as the new construction?

Yes.

Who performed the construction seismic retrofit measures: a contractor, or owner/user? Was an architect or engineer involved?

The owner - no architects or engineers are involved.

What was the performance of retrofitted buildings of this type in subsequent earthquakes?

N/A.

Reference(s)

1. Seismicity and Source Mechanisms of the Malawi Rift and Adjacent Areas, from 1900 to 1990
Chapola, L.S.

for the course of seismology 1990-1991 at International Institute of Seismology and Earthquake Engineering, Building Research Institute Tsukuba, Japan 1991

2. The Malawi Earthquake of March,10, 1989: A Report of Macro seismic Survey
Gupta,H.K.
Tectonophy 209, No. 1-4, 165-166 1992
3. An Estimation of Earthquake Hazards and Risks in Malawi
Chapola,L.S.
Geological Surveys Department, P.O. Box 27, Zomba 1993
4. Seismicity and Tectonics of Malawi
Chapola,L.S.
National Atlas of Malawi 1994
5. State of Stress in East and Southern Africa and Seismic Hazard Analysis of Malawi
Chapola,L.S.
M.Sc. Thesis, Institute of Solid Earth Physics, University of Bergen, Norway 1997
6. National Housing Policy
Malawi Government 1999
7. Low Cost Building Materials in Malawi
Kamwanja,G.A.
Ph.D. Thesis, University of Malawi 1988

Author(s)

1. Mauro Sassu
Associate Professor, Dept. of Structural Engineering, University of Pisa
Via Diotisalvi 2, Pisa 56126, ITALY
Email:m.sassu@ing.unipi.it FAX: 39 050 554597
2. Ignasio Ngoma
Senior Lecturer, University of Malawi
The Polytechnic P/B 303, Blantyre 3, MALAWI
Email:ingoma@poly.sdn.org.mw FAX: 265-670578

Reviewer(s)

1. Manuel A. Lopez M.
Engineer
Escuela de Ingenier, Universidad de El Salvador
San Salvador , EL SALVADOR
Email:manuel.lopez@unipv.it FAX: 503-225-2506

Save page as

