
World Housing Encyclopedia

*an Encyclopedia of Housing Construction in
Seismically Active Areas of the World*



an initiative of
Earthquake Engineering Research Institute (EERI) and
International Association for Earthquake Engineering (IAEE)

HOUSING REPORT

Single-storey brick masonry house (EMSB1)

Report #	91
Report Date	17-03-2003
Country	BANGLADESH
Housing Type	Unreinforced Masonry Building
Housing Sub-Type	Unreinforced Masonry Building : Brick masonry in lime/cement mortar
Author(s)	Mehedi Ansary
Reviewer(s)	Alpa R. Sheth

Important

This encyclopedia contains information contributed by various earthquake engineering professionals around the world. All opinions, findings, conclusions & recommendations expressed herein are those of the various participants, and do not necessarily reflect the views of the Earthquake Engineering Research Institute, the International Association for Earthquake Engineering, the Engineering Information Foundation, John A. Martin & Associates, Inc. or the participants' organizations.

Summary

This is a one-story brick masonry house of fired bricks with cement or lime mortar; roof is either GI sheet or another material. These houses can be seen throughout Bangladesh. During the 1918 Srimangal, 1930 Dhubri, and other recent earthquakes, this type of housing suffered heavy damage. Houses with a continuous lintel suffered less.

1. General Information

Buildings of this construction type can be found in all parts of Bangladesh. This type of housing construction is commonly found in both rural and urban areas. This construction type has been in practice for less than 100 years.

Currently, this type of construction is being built.

2. Architectural Aspects

2.1 Siting

These buildings are typically found in flat terrain. They do not share common walls with adjacent buildings. In the villages this type of housing may be located several 100 meters apart. When separated from adjacent buildings, the typical distance from a neighboring building is 2 meters.

2.2 Building Configuration

Mostly L-shaped, sometimes rectangular. At least three for a single room (two windows and one door). The buildings generally comprise of two to three rooms. The inner and outer rooms have at least two doors. Opening per wall is around 20%. Doors and windows are located in the middle of the wall.

2.3 Functional Planning

The main function of this building typology is single-family house. In a typical building of this type, there are no elevators and 1-2 fire-protected exit staircases. No.

2.4 Modification to Building




Figure 1: Typical plan

3. Structural Details

3.1 Structural System

Material	Type of Load-Bearing Structure	#	Subtypes	Most appropriate type
			Rubble stone (field stone) in mud/lime	

Masonry	Stone Masonry Walls	1	mortar or without mortar (usually with timber roof)	<input type="checkbox"/>
		2	Dressed stone masonry (in lime/cement mortar)	<input type="checkbox"/>
	Adobe/ Earthen Walls	3	Mud walls	<input type="checkbox"/>
		4	Mud walls with horizontal wood elements	<input type="checkbox"/>
		5	Adobe block walls	<input type="checkbox"/>
		6	Rammed earth/Pise construction	<input type="checkbox"/>
	Unreinforced masonry walls	7	Brick masonry in mud/lime mortar	<input type="checkbox"/>
		8	Brick masonry in mud/lime mortar with vertical posts	<input type="checkbox"/>
		9	Brick masonry in lime/cement mortar	<input checked="" type="checkbox"/>
		10	Concrete block masonry in cement mortar	<input type="checkbox"/>
	Confined masonry	11	Clay brick/tile masonry, with wooden posts and beams	<input type="checkbox"/>
		12	Clay brick masonry, with concrete posts/tie columns and beams	<input type="checkbox"/>
		13	Concrete blocks, tie columns and beams	<input type="checkbox"/>
	Reinforced masonry	14	Stone masonry in cement mortar	<input type="checkbox"/>
		15	Clay brick masonry in cement mortar	<input type="checkbox"/>
		16	Concrete block masonry in cement mortar	<input type="checkbox"/>
Structural concrete	Moment resisting frame	17	Flat slab structure	<input type="checkbox"/>
		18	Designed for gravity loads only, with URM infill walls	<input type="checkbox"/>
		19	Designed for seismic effects, with URM infill walls	<input type="checkbox"/>
		20	Designed for seismic effects, with structural infill walls	<input type="checkbox"/>
		21	Dual system – Frame with shear wall	<input type="checkbox"/>
	Structural wall	22	Moment frame with in-situ shear walls	<input type="checkbox"/>
		23	Moment frame with precast shear walls	<input type="checkbox"/>
	Precast concrete	24	Moment frame	<input type="checkbox"/>
		25	Prestressed moment frame with shear walls	<input type="checkbox"/>
		26	Large panel precast walls	<input type="checkbox"/>
		27	Shear wall structure with walls cast-in-situ	<input type="checkbox"/>
		28	Shear wall structure with precast wall panel structure	<input type="checkbox"/>
29		With brick masonry partitions	<input type="checkbox"/>	
Steel	Moment-resisting frame	30	With cast in-situ concrete walls	<input type="checkbox"/>
		31	With lightweight partitions	<input type="checkbox"/>
		32	Concentric connections in all panels	<input type="checkbox"/>
	Braced frame	33	Eccentric connections in a few panels	<input type="checkbox"/>
		34	Bolted plate	<input type="checkbox"/>
	Structural wall	35	Welded plate	<input type="checkbox"/>
		36	Thatch	<input type="checkbox"/>

Timber	Load-bearing timber frame	37	Walls with bamboo/reed mesh and post (Wattle and Daub)	<input type="checkbox"/>
		38	Masonry with horizontal beams/planks at intermediate levels	<input type="checkbox"/>
		39	Post and beam frame (no special connections)	<input type="checkbox"/>
		40	Wood frame (with special connections)	<input type="checkbox"/>
		41	Stud-wall frame with plywood/gypsum board sheathing	<input type="checkbox"/>
		42	Wooden panel walls	<input type="checkbox"/>
Other	Seismic protection systems	43	Building protected with base-isolation systems	<input type="checkbox"/>
		44	Building protected with seismic dampers	<input type="checkbox"/>
	Hybrid systems	45	other (described below)	<input type="checkbox"/>

Tie columns are not used.

3.2 Gravity Load-Resisting System

The vertical load-resisting system is earthen walls. Traditionally, 10 inch wall is used as load bearing walls. But sometimes poor people use 5 inch wall. Poorer construction do not have any kind of plaster.

3.3 Lateral Load-Resisting System

The lateral load-resisting system is earthen walls. Sometimes there is a continuous lintel, sometimes none. In earthquake prone areas like Chittagong, Sylhet etc. approximately 50% private housing units have continuous lintel. But on the government buildings, the percentage is much lower.

3.4 Building Dimensions

The typical plan dimensions of these buildings are: lengths between 3 and 5 meters, and widths between 2 and 4 meters. The building is 1 storey high. The typical span of the roofing/flooring system is 3 meters. The typical storey height in such buildings is 2.8 meters. The typical structural wall density is up to 20%. 15 - 20%.

3.5 Floor and Roof System

Material	Description of floor/roof system	Most appropriate floor	Most appropriate roof
Masonry	Vaulted	<input type="checkbox"/>	<input type="checkbox"/>
	Composite system of concrete joists and masonry panels	<input type="checkbox"/>	<input type="checkbox"/>
Structural concrete	Solid slabs (cast-in-place)	<input type="checkbox"/>	<input type="checkbox"/>
	Waffle slabs (cast-in-place)	<input type="checkbox"/>	<input type="checkbox"/>
	Flat slabs (cast-in-place)	<input type="checkbox"/>	<input type="checkbox"/>
	Precast joist system	<input type="checkbox"/>	<input type="checkbox"/>
	Hollow core slab (precast)	<input type="checkbox"/>	<input type="checkbox"/>
	Solid slabs (precast)	<input type="checkbox"/>	<input type="checkbox"/>
	Beams and planks (precast) with concrete topping (cast-in-situ)	<input type="checkbox"/>	<input type="checkbox"/>
Slabs (post-tensioned)	<input type="checkbox"/>	<input type="checkbox"/>	
Steel	Composite steel deck with concrete slab (cast-in-situ)	<input type="checkbox"/>	<input type="checkbox"/>
	Rammed earth with ballast and concrete or plaster finishing	<input type="checkbox"/>	<input type="checkbox"/>

Timber	Wood planks or beams with ballast and concrete or plaster finishing	<input type="checkbox"/>	<input type="checkbox"/>
	Thatched roof supported on wood purlins	<input type="checkbox"/>	<input type="checkbox"/>
	Wood shingle roof	<input type="checkbox"/>	<input type="checkbox"/>
	Wood planks or beams that support clay tiles	<input type="checkbox"/>	<input type="checkbox"/>
	Wood planks or beams supporting natural stones slates	<input type="checkbox"/>	<input type="checkbox"/>
	Wood planks or beams that support slate, metal, asbestos-cement or plastic corrugated sheets or tiles	<input type="checkbox"/>	<input type="checkbox"/>
	Wood plank, plywood or manufactured wood panels on joists supported by beams or walls	<input type="checkbox"/>	<input type="checkbox"/>
Other	Described below	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

GI roofs with purlins.

3.6 Foundation

Type	Description	Most appropriate type
Shallow foundation	Wall or column embedded in soil, without footing	<input checked="" type="checkbox"/>
	Rubble stone, fieldstone isolated footing	<input type="checkbox"/>
	Rubble stone, fieldstone strip footing	<input type="checkbox"/>
	Reinforced-concrete isolated footing	<input type="checkbox"/>
	Reinforced-concrete strip footing	<input type="checkbox"/>
	Mat foundation	<input type="checkbox"/>
	No foundation	<input type="checkbox"/>
Deep foundation	Reinforced-concrete bearing piles	<input type="checkbox"/>
	Reinforced-concrete skin friction piles	<input type="checkbox"/>
	Steel bearing piles	<input type="checkbox"/>
	Steel skin friction piles	<input type="checkbox"/>
	Wood piles	<input type="checkbox"/>
	Cast-in-place concrete piers	<input type="checkbox"/>
	Caissons	<input type="checkbox"/>
Other	Described below	<input type="checkbox"/>

Stepped brick foundations with cement mortars are used. Generally foundation bottom lies 2 to 3 ft below GL.



Figure 2: Typical Construction

4. Socio-Economic Aspects

4.1 Number of Housing Units and Inhabitants

Each building typically has 1 housing unit(s). 1 units in each building. The number of inhabitants in a building during the day or business hours is less than 5. The number of inhabitants during the evening and night is 5-10.

4.2 Patterns of Occupancy

As the joint family tradition is strong in the rural areas, an extended family occupy the housing unit. Typically, the families comprise of a father and two-three sons. As the family further expands, the sons families occupy independent units.

4.3 Economic Level of Inhabitants

Income class	Most appropriate type
a) very low-income class (very poor)	<input type="checkbox"/>
b) low-income class (poor)	<input type="checkbox"/>
c) middle-income class	<input checked="" type="checkbox"/>
d) high-income class (rich)	<input checked="" type="checkbox"/>

The middle class housing unit roughly costs USD 1,000, on the other hand the rich housing unit costs USD 1,500 to 2,000.

Ratio of housing unit price to annual income	Most appropriate type
5:1 or worse	<input type="checkbox"/>
4:1	<input type="checkbox"/>
3:1	<input type="checkbox"/>
1:1 or better	<input checked="" type="checkbox"/>

What is a typical source of financing for buildings of this type?	Most appropriate type
Owner financed	<input checked="" type="checkbox"/>
Personal savings	<input checked="" type="checkbox"/>
Informal network: friends and relatives	<input type="checkbox"/>
Small lending institutions / micro-finance institutions	<input checked="" type="checkbox"/>
Commercial banks/mortgages	<input type="checkbox"/>
Employers	<input type="checkbox"/>
Investment pools	<input type="checkbox"/>
Government-owned housing	<input type="checkbox"/>
Combination (explain below)	<input type="checkbox"/>
other (explain below)	<input type="checkbox"/>

In each housing unit, there are 1 bathroom(s) without toilet(s), 1 toilet(s) only and 1 bathroom(s) including toilet(s).

4.4 Ownership

The type of ownership or occupancy is renting and outright ownership.

Type of ownership or occupancy?	Most appropriate type
Renting	<input checked="" type="checkbox"/>
outright ow nership	<input checked="" type="checkbox"/>
Ow nership with debt (mortgage or other)	<input type="checkbox"/>
Individual ow nership	<input type="checkbox"/>
Ow nership by a group or pool of persons	<input type="checkbox"/>
Long-term lease	<input type="checkbox"/>
other (explain below)	<input type="checkbox"/>

5. Seismic Vulnerability

5.1 Structural and Architectural Features

Structural/ Architectural Feature	Statement	Most appropriate type		
		Yes	No	N/A
Lateral load path	The structure contains a complete load path for seismic force effects from any horizontal direction that serves to transfer inertial forces from the building to the foundation.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Building Configuration	The building is regular with regards to both the plan and the elevation.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Roof construction	The roof diaphragm is considered to be rigid and it is expected that the roof structure will maintain its integrity, i.e. shape and form, during an earthquake of intensity expected in this area.	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Floor construction	The floor diaphragm(s) are considered to be rigid and it is expected that the floor structure(s) will maintain its integrity during an earthquake of intensity expected in this area.	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Foundation performance	There is no evidence of excessive foundation movement (e.g. settlement) that would affect the integrity or performance of the structure in an earthquake.	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Wall and frame structures-redundancy	The number of lines of walls or frames in each principal direction is greater than or equal to 2.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wall proportions	Height-to-thickness ratio of the shear walls at each floor level is: Less than 25 (concrete walls); Less than 30 (reinforced masonry walls); Less than 13 (unreinforced masonry walls);	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Foundation-wall connection	Vertical load-bearing elements (columns, walls) are attached to the foundations; concrete columns and walls are doweled into the foundation.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Wall-roof connections	Exterior walls are anchored for out-of-plane seismic effects at each diaphragm level with metal anchors or straps	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	The total width of door and window openings in a wall is: For brick masonry construction in cement mortar : less than 1/2 of the distance between the adjacent cross walls;			

Wall openings	For adobe masonry, stone masonry and brick masonry in mud mortar: less than 1/3 of the distance between the adjacent cross walls; For precast concrete wall structures: less than 3/4 of the length of a perimeter wall.	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Quality of building materials	Quality of building materials is considered to be adequate per the requirements of national codes and standards (an estimate).	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Quality of workmanship	Quality of workmanship (based on visual inspection of few typical buildings) is considered to be good (per local construction standards).	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Maintenance	Buildings of this type are generally well maintained and there are no visible signs of deterioration of building elements (concrete, steel, timber)	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Additional Comments				

5.2 Seismic Features

Structural Element	Seismic Deficiency	Earthquake Resilient Features	Earthquake Damage Patterns
Wall	Weak from earthquake point of view; sometimes there are no plaster; lack of lintel bands; no measures to strengthen the corners.		
Frame (Columns, beams)			
Roof and floors			
Other	Lack of awareness about the earthquake resistant construction practices.		

5.3 Overall Seismic Vulnerability Rating

The overall rating of the seismic vulnerability of the housing type is *B: MEDIUM-HIGH VULNERABILITY (i.e., poor seismic performance)*, the lower bound (i.e., the worst possible) is *A: HIGH VULNERABILITY (i.e., very poor seismic performance)*, and the upper bound (i.e., the best possible) is *C: MEDIUM VULNERABILITY (i.e., moderate seismic performance)*.

Vulnerability	high	medium-high	medium	medium-low	low	very low
	very poor	poor	moderate	good	very good	excellent
Vulnerability Class	A	B	C	D	E	F
	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

5.4 History of Past Earthquakes

Date	Epicenter, region	Magnitude	Max. Intensity
1885	Bogra-Sirajganj	7	VIII
1897	Assam	8	X
		7.6	

1918	Srimangal		VIII
1997	Bangladesh-India Border	5.6	VII

During the 1897 Assam earthquake, almost 90% of this type of structure suffered some kind of damage.




Figure 3: Damage at Rangpur, 1897 earthquake




Figure 4: Damage at Sirajganj, 1897 Earthquake




Figure 5: elevation of typical building



Figure 6: Damage due to 2003 Rangamati Earthquake

6. Construction

6.1 Building Materials

Structural element	Building material	Characteristic strength	Mix proportions/ dimensions	Comments
Walls	Brick, cement mortar		1:4 (cement: sand)	
Foundation	Brick, cement mortar		1:4 (cement: sand)	
Frames (beams & columns)				
Roof and floor(s)				

6.2 Builder

The house owners hire masons to build these houses. Sometimes masons live in similar houses.

6.3 Construction Process, Problems and Phasing

- trench line is planned - excavate 2 to 3 ft deep trench - 6 inch thick sand layer - lay brick and use cement mortar to join them. The construction of this type of housing takes place in a single phase. Typically, the building is originally not designed for its final constructed size. Sometimes new rooms are constructed for the extended family.

6.4 Design and Construction Expertise

No formal training. Masons are trained by their seniors. Owners are the architect and masons are the engineer for this

type of housing. They do not have a large role, but masons can be trained by the engineers according to the code guideline for construction.

6.5 Building Codes and Standards

This construction type is addressed by the codes/standards of the country. Bangladesh National Building Code. The year the first code/standard addressing this type of construction issued was 1993. BNBC 1993. Title of the code or standard: Bangladesh National Building Code. Year the first code/standard addressing this type of construction issued: 1993 National building code, material codes and seismic codes/standards: BNBC 1993.

There is no enforcement of building codes for this type of construction.

6.6 Building Permits and Development Control Rules

This type of construction is a non-engineered, and not authorized as per development control rules.

There are no guidelines for this type of housing. No prior approval is required. Building permits are not required to build this housing type.

6.7 Building Maintenance

Typically, the building of this housing type is maintained by Owner(s).

6.8 Construction Economics

Total project: US Dollar 50/sq m. The labor requirements for a typical house of about 30 to 50 sq.m are about 100 to 120 man-days.

7. Insurance

Earthquake insurance for this construction type is typically unavailable. For seismically strengthened existing buildings or new buildings incorporating seismically resilient features, an insurance premium discount or more complete coverage is unavailable.

8. Strengthening

8.1 Description of Seismic Strengthening Provisions

Strengthening of Existing Construction :

Seismic Deficiency	Description of Seismic Strengthening provisions used
Inadequate wall resistance due to the absence of seismic provisions	Covering the wall with 1 ft wide seismic belt (steel wire mesh with cement mortar) at lintel level on both sides of the wall.

Strengthening of New Construction :

Seismic Deficiency	Description of Seismic Strengthening provisions used
Foundations	Provision of strip foundation
Walls	Provision of RC ring beams at plinth, lintel etc. levels. Provision of vertical steel reinforcement bars at the wall corners and intersections.

8.2 Seismic Strengthening Adopted

Has seismic strengthening described in the above table been performed in design and construction practice, and if so, to what extent?

Proposed for the damaged buildings of 2003 Rangamati earthquake.

Was the work done as a mitigation effort on an undamaged building, or as repair following an earthquake?

N/A.

8.3 Construction and Performance of Seismic Strengthening

Was the construction inspected in the same manner as the new construction?

N/A.

Who performed the construction seismic retrofit measures: a contractor, or owner/user? Was an architect or engineer involved?

N/A.

What was the performance of retrofitted buildings of this type in subsequent earthquakes?

N/A.




Figure 7: Typical foundation

Reference(s)

1. Seismic Risk of Five Selected Cities of Bangladesh
Ansary, M.A.
CARE-Bangladesh, BUET. February 2003
2. Bangladesh National Building Code, 1993

3. Guidelines for Earthquake Resistant Non-engineered Construction
IAEE

Author(s)

1. Mehedi Ansary
Doctor, Department of Civil Engineering, Bangladesh University of Engineering & Technology
Department of Civil Engineering, Bangladesh University of Engineering & Technology, Dhaka 1000, BANGLADESH
Email:ansaryma@yahoo.com FAX: 8802-8613026

Reviewer(s)

1. Alpa R. Sheth
Partner
, Vakil Mehta Sheth Consulting Engineers
Mumbai 400023, INDIA
Email:alpa_sheth@vsnl.com FAX: (91-22) 2284 3735

Save page as

