INDIA: Summary of Building Types, Vulnerability to Collapse and Occupancy

Completed by**:** C.V. R. Murty, Indian Institute of Technology, Kanpur, Department of Civil Engineering, IIT Kanpur, Kanpur 208016, India; E-mail address:cvrm@iitk.ac.in

List construction type *(refer to Tables 2 and 3 for suggested categories, sources of data to help answer this question)*	**Probability of collapse (%) building type when subjected to the specified shaking intensity (*refer to instructions on page 5*)**				**Fraction of population who LIVES in this building type** (*refer to instructions on page 5 for help in estimating*)		**Fraction of population who WORKS in this building type** (*refer to instructions on page 5 for help in estimating*)		**Peak average number of occupants per building** *refer to instructions on page 5 for help in estimating*)
	MMI/MSK IX (~0.65-1.24g)	**MMI/MSK VIII (~0.34-0.65g)**	**MMI/MSK VII (~0.18-0.34g)**	**MMI/MSK VI (~0.092-.18g)**	**urban areas**	**rural areas**	**Urban areas**	**rural areas**	
Mud and Unburnt Brick Houses	100	100	90	60	**11.2**	**37.1**	3	20	8
Stone Masonry Houses	100	95	60	45	**7.2**	**11.5**	20	4	6
Grass, Thatch, Bamboo, etc., Houses	95	80	50	20	**3.6**	**12.5**	1	4	5
Unreinforced Clay Brick Masonry Wall Houses	85	65	40	10	**68.7**	**35.3**	35	25	4
RC Moment resisting frame buildings (Gravity Designed Frame)	65	30	15	0	**6.0**	**1.3**	40	0	80