GERMANY: Summary of Building Types, Vulnerability to Collapse and Occupancy

Completed by**:** Sergey Tyagunov, Lothar Stempniewski, Christian Münich, Center for Disaster Management and Risk Reduction Technology—DEDIM, Institute of Concrete Structures, University of Karlsruhe, Institut für Massivbau, Karlsruhe Universität, 76128, Karlsruhe, Germany. E-mails: sergey.tyagunov@ifmb.uni-karlsruhe.de; lothar.stempniewski@ifmb.uni-karlsruhe.de; christian.muenich@ifmb.uni-karlsruhe.de

WHE Construction Type refer to Table 2 for suggested category(ies)	Description of construction type (refer to Tables 2 and 3 for suggested categories and sources of data to help answer this question) (2)	Probability of collapse (%) building type when subjected to the specified shaking intensity (refer to instructions page 5) (3) MMI / EMS / MSK				Fraction of population who LIVES in this building type (*refer to instructions for help in estimating*)		Fraction of population who WORKS in this building type (refer to instructions on page 5 for help in estimating)		Peak average number of occupants per building (refer to instructions on page 5 for help in estimating) (8)
(1)		IX (~0.65-1.24g)	VIII (~0.34-0.65g)	VII (~0.18-0.34g)	VI (~0.092-.18g)	urban areas (4)	rural areas (5)	urban areas (6)	rural areas (7)	
2	Stone masonry walls	30-60	5-20	0-2	0	Very low	Low	Very low	Very low	?
9	Unreinforced brick masonry in cement mortar (various floor/roof systems)	10-30	2-10	0-1	0	Moderate	Moderate	Moderate	Moderate	?
11	Unreinforced concrete block masonry in cement mortar (various floor/roof systems)	10-30	2-10	0-1	0	Low	Low	Low	Low	?
12	Reinforced masonry , in cement mortar (various floor/roof systems)	5-20	1-5	0	0	Low	Low	Low	Low	?
16	RC frame with unreinforced masonry infill walls	5-20	1-5	0	0	Moderate	Low	Moderate	Moderate	?